

XPS-I551SP

2 port 10/100/1000 PoE + 1 port 100/1000 SFP Industrial PoE Switch



- 10/100/1000BaseT
- 100/1000 SFP
- Total PoE Budget: 60 W
- IEEE802.3af/at
- Auto MDI/MDIX
- Auto-Negotiation
- IEEE802.3x
- LFPT

Technical Specs.

Model No	XPS-I551SP
Port Types	2x RJ45 copper PoE ports (Auto Uplink) + 1 SFP port

Performance

Switching Capacity	6 Gbps
Forwarding Rate	4.46 Mmps

Features

IEEE 802.3	IEEE 802.3af
IEEE 802.3i	IEEE 802.3at
IEEE 802.3u	Store and Forward
Auto-Negotiation	Link Fault Pass Through

Environment

DC Power Input	47-55V
Power Consumption	65W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95%, non-condensing

Mechanical

Dimension	119 x 100 x 30 mm
Weight	0.38 kg
Installation	IP40 rating, DIN-Rail

Standards and Protocols

CE mark, commercial	EN61000-3-2	EN61000-4-6
VCCI Class B	EN61000-3-3	EN61000-4-8
FCC Part 15 Class B	EN61000-4-2	IEC60068-2-6
CE/LVD EN60950	EN61000-4-3	EN61000-6-2
ISO 9001	EN61000-4-4	EN61000-6-4
EN 55022 (CISPR 22), Class B	EN61000-4-5	IEC60068-2-27 Ea

Ordering Information

XPS-I551SP	2 port 10/100/1000 PoE + 1 port 100/1000 SFP Industrial PoE Switch
-------------------	--

Modules

XPS-I21LX	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
XPS-I21SX	XPS Industrial Dual Core SX MM SFP Module -40/75°C

*more module ranges are available upon request.